

Freya Motorcycle Cover Care & Fitting Instructions



The Viking 'Freya' range of motorcycle covers have been developed to bring to you the ultimate quality in stretch dust covers that are available today. Our covers utilise modern polar fleece fabrics that combines baby softness and breathability with strength and durability. Your cover has been produced in our UK factory with care to ensure long life and protection for your bike. The soft fabric protects from dust and dirt and those annoying little scratches that can occur in the garage.

Freya Motorcycle Cover Features

- Fully breathable water resistant fabric allows moisture & damp to escape
- Super soft stretch fabric accentuates vehicle profile & lines
- Completely non-scratch soft cover ensures maximum paintwork protection
- Elasticated front and rear hems for snug fit with stitched in 'front' label for ease of fitting
- Comprehensive range of cover and piping colours available
- Washable & supplied with washing instructions
- 100% ultraviolet resistant fabric to prevent paint fade
- Manufactured purely to your motorcycle's specification
- Separate generous sized sturdy zipped storage bag.
- 1 year standard warranty against faulty materials or workmanship
- Optional accidental damage enhanced warranty available



Cover Fitting Guide

We want you to enjoy maximum life and protection from your new cover. Here are a few common sense tips to ensure that your car receives ultimate protection:

Dirt, grit & water are your cars enemies. Always ensure that you cover a clean, cool, dry bike. Dirt and grit particles on paintwork can act as abrasives & will produce unsightly scratches in the paintwork.

When fitting the cover ensure that the engine heat has cooled from the bodywork, that you avoid contact with hot exhausts and that everything is cool and dry.

Aerials/radio antennas should be retracted or removed prior to fitment of your bike cover. All our covers have been designed to assist airflow around your bike by use of breathable fabrics. However, if the bike is kept in an environment where condensation might occur or it is subjected to a prolonged period of damp, check the condition of your motorcycle and cover on a weekly basis. Pull back the cover, inspect the paintwork and the inside of the cover and ensure that the car and fabric are completely dry. If any damp is present, the motorcycle and cover need to be aired and dried.

If you are using the cover for a long period of time we advise stretching the elastic hems on a regular basis to keep the elastic in good condition.

Best Fitting Tips

1. Unfold the cover & find the 'front' label that is stitched into the elasticated hem at one end of the cover.
2. Position the bike cover with 'front' label to inside over front end of bike and arrange the cover over handles & seat of bike.
3. Finally fit rear of cover.
4. Connect centre strap fastener
5. Special care should be taken when fastening the strap to ensure it does not touch hot components.
6. **DO NOT PULL TIGHT.** The cover should be able to move freely to allow air circulation under the cover.

Do not fit a cover to a bike that has been re-painted in the last 3-6 months. Ask your repair shop for advice. (excludes new bike original paint)

Keep your cover away from naked flames and sources of ignition. Store in the storage bag provided when not in use.

Cover Removal & Storage

To remove & refold the cover, release the centre strap, elasticated hems & bring the sides together. Fold the cover in half and in half again. This process keeps the dirty outer away from the clean inner surface! Store your cover in the bag provided when not in use. If the cover is wet, thoroughly line dry & air before storing in the bag.

Care & Washing Instructions

Your new cover will reach you in perfect condition. However, with the passing of time it may become dirty and grubby. Care should be taken when washing and the following guidelines should be observed:

Hand wash in cold or hand warm water using a mild washing liquid. Take care to rinse thoroughly several times. Do not use detergents that include bleach or fabric softeners. Line dry until completely dry. **Do not iron!**

Freya covers may be washed in domestic washing machines, subject to size. Select a gentle cycle with a maximum temperature of 30 degrees centigrade and use a mild washing liquid as above. Ensure several rinses and a gentle spin speed. Line dry until completely dry.



Do's

- ✓ Always fit your cover on clean, dry bike
- ✓ Allow engine & exhausts to cool
- ✓ Remove/retract antennas & pad the base plate
- ✓ Remove cover regularly to check condition of the bike
- ✓ Allow cover to dry before storing
- ✓ Wash in cold or warm water
- ✓ Remove cover regularly to check condition of bike

Don'ts

- ✗ Use outdoors
- ✗ Fit on a newly repainted bike
- ✗ Use of a trailer
- ✗ Wash in hot water
- ✗ Dry clean
- ✗ Tumble dry
- ✗ Wring tightly
- ✗ Iron
- ✗ Fit to a wet bike

If you discover bird muck on your cover you must wash it off straight away as the cover fabric may start to degrade due to the acidity of bird lime.

Following these simple guidelines will ensure that your bike cover will last for many years and provide the maximum protection.

Motorcycle Cover Enhanced Warranty Option (1 Year or 3 Year Cover)

Your new cover has a one year warranty against manufacturing defects or faulty materials. Accidental damage and damage caused by rodents or pests is not covered.

At Viking Covers we understand that household and motor insurers may be reluctant to reimburse you for damage sustained to motorcycle covers & consequently we offer an optional enhanced warranty ourselves.

The enhanced warranty covers accidental damage to the cover (but not to the bike) tears & rips caused through storm damage, sunshine damage and damage caused by pets, animals & birds. This is not an insurance policy & theft/vandalism are excluded.

This cover is designed for indoor use and damage caused outdoors is excluded from the guarantee and extended warranty.

